

**National Examinations – May 2018**

**16-Civ-B10, Traffic Engineering**

**3 Hour Duration**

**NOTES**

1. If doubt exists as to the interpretation of any question, the candidate is urged to submit with the answer book a clear statement of any assumptions made.
2. Any data required, but not given, can be assumed.
3. This is an “**OPEN BOOK**” examination. Any non-communicating calculator is permitted.
4. A total of **five** solutions is required. Only the first five as they appear in your answer book will be marked.
5. All questions are of equal value.

**Grading Scheme:**

Question 1 (a) to (e) – 4 marks each

Question 2 – 20 marks

Question 3 (a) to (e) – 4 marks each

Question 4 (a) to (h) – 2.5 marks each

Question 5 (a) – 6 marks, (b) and (c) – 7 marks each

Question 6 (a) to (e) – 4 marks each

Question 7 – 20 marks

1. Define and discuss each of the following:
  - a) Bicycle lanes vs. bicycle paths
  - b) Cordon counts vs. screenline counts
  - c) Leading protected phase vs. lagging protected phase
  - d) Protected phase vs. permissive phase
  - e) Time mean speed (TMS) vs. Space mean speed (SMS)
  
2. For the traffic pattern shown in the tables below, determine an appropriate signal phasing system and phase lengths for the intersection using the Webster method. Show a detailed layout of the phasing system and the intersection geometry used. Assume lost time per phase due to acceleration and deceleration at phase changes is 3.5 seconds and that an all-red interval of 1.5 seconds is provided at each phase.

Approach (Width)	North (12 m)	South (12 m)	East (15 m)	West (15 m)
<b>Peak hour approach volumes</b>				
Left turn	300	201	300	201
Through movement	712	600	615	850
Right turn	243	395	255	300
Conflicting pedestrian volumes per hour	1150	1150	1250	1050
PHF	0.95	0.95	0.95	0.95

Lane type	Saturation Flows (vphpl)
Through	2675
Through-right	2010
Left	1835
Left-through	1800
Left-through-right	1725

3. The following table shows collected data using the moving vehicle method of estimating traffic volume and travel time studies. Using this data compute:

- All average values for both southbound and northbound trips.
- Northbound traffic volume (vehicles/hour)
- Southbound traffic volume (vehicles/hour)
- Average travel time of Northbound traffic (minutes)
- Average travel time of Southbound traffic (minutes)

Run Direction / Number	Travel time (min)	No. of vehicles traveling in Opposite Direction	No. of vehicles that overtook the test vehicle	No. of vehicles overtaken by the test vehicle
<b>Southbound</b>				
1	4.55	162	3	2
2	4.20	155	4	3
3	4.72	178	2	3
4	4.42	157	4	3
5	5.21	174	1	2
6	5.26	166	3	3
7	4.92	187	3	2
8	4.75	160	4	2
<b>Northbound</b>				
1	4.03	139	3	2
2	4.27	163	2	3
3	4.41	162	1	3
4	3.89	141	4	2
5	4.19	135	2	1
6	3.71	157	3	2
7	4.44	166	2	2
8	4.15	156	3	3

4. An approach at a signalized intersection has a saturation flow of 2750 vph and the flow of the approach traffic is 550 vph. If the cycle time is 85 second with a 30 second effective green determine the following values using D/D/1 queuing:

- Verify that the capacity is greater than the arrival rate
- Time to queue clearance after the start of the effective green
- Proportion of the cycle with a queue
- Proportion of vehicles stopped
- Maximum number of vehicles in the queue
- Total vehicle delay per cycle
- Average delay per vehicle
- Maximum delay of any vehicle

## 5. Curves

Design speed (km/h)	Metric				US Customary				
	Brake reaction distance (m)	Braking distance on level (m)	Stopping sight distance		Design speed (mph)	Brake reaction distance (ft)	Braking distance on level (ft)	Stopping sight distance	
			Calculated (m)	Design (m)				Calculated (ft)	Design (ft)
20	13.9	4.6	18.5	20	15	55.1	21.6	76.7	80
30	20.9	10.3	31.2	35	20	73.5	38.4	111.9	115
40	27.8	18.4	46.2	50	25	91.9	60.0	151.9	155
50	34.8	28.7	63.5	65	30	110.3	86.4	196.7	200
60	41.7	41.3	83.0	85	35	128.6	117.6	246.2	250
70	48.7	56.2	104.9	105	40	147.0	153.6	300.6	305
80	55.6	73.4	129.0	130	45	165.4	194.4	359.8	360
90	62.6	92.9	155.5	160	50	183.8	240.0	423.8	425
100	69.5	114.7	184.2	185	55	202.1	290.3	492.4	495
110	76.5	138.8	215.3	220	60	220.5	345.5	566.0	570
120	83.4	165.2	248.6	250	65	238.9	405.5	644.4	645
130	90.4	193.8	284.2	285	70	257.3	470.3	727.6	730
					75	275.6	539.9	815.5	820
					80	294.0	614.3	908.3	910

Note: Brake reaction distance predicated on a time of 2.5 s; deceleration rate of 3.4 m/s<sup>2</sup> [11.2 ft/s<sup>2</sup>] used to determine calculated sight distance.

Source: AASHTO, 2001

- a) Define Perception-Reaction Time and Braking Distance
  - b) A section of road is being designed with a vertical crest curve to join an entering grade of 2% grade to a departing -4% grade with a design speed of 50 km/h. Determine the minimum length of the curve that will provide adequate stopping sight distance. Assume that the driver's height is 1050 mm and the stopping sight distance is to be designed for small objects in the road with an average height of 500 mm.
  - c) A 125 m vertical crest curve is designed to connect a +3% tangent with a -1% tangent. What should the design speed be to provide ample stopping sight distance? Use standard heights for the driver and object of 1080 mm and 625 mm, respectively.
6. A shopping store has only one cashier where customers arrive at a rate of 5 per 10 minutes. The cashier processes these customers at a mean service rate of 6 customers per 10 minutes.
    - (a) What is the probability that the cashier is free?
    - (b) How many customers on average are waiting to be processed?
    - (c) Calculate the average number of customers in line.
    - (d) Calculate the average wait time for a customer and the average time a customer spends being processed by the cashier.
    - (e) If the line of customers is longer than 3 customers, a second cashier is opened, what is the probability of a second cashier being opened?
  7. Repeat question 2 given that the saturation flow rates are 15% lower and the pedestrian flow rates are 5% lower. How do these decreases effect the cycle length?