

**National Examinations – May 2016****98-Civ-B7, Highway Engineering****3 Hour Duration****NOTES**

1. If doubt exists as to the interpretation of any question, the candidate is urged to submit with the answer paper a clear statement of any assumptions made.
2. Any data, not given but required, can be assumed.
3. This is an “**OPEN BOOK**” examination. Any non-communicating calculator is permitted.
4. A total of **five** solutions is required. Only the first five as they appear in your answer book will be marked.
5. All questions are of equal value.
6. For non-numerical questions, clarity and organization of the answer are important.

**Marking Scheme**

1. (a) 15 marks.  
(b) 5 marks.
2. 20 marks.
3. (a) 6 marks.  
(b) 14 marks.
4. 20 marks.
5. (a) 10 marks.  
(b) 10 marks.
6. (a) 12 marks  
(b) 8 marks.
7. (a) 7 marks  
(b) 7 marks  
(c) 6 marks

1. (a) A vertical curve is to be designed to join a +1.5% and -2% grade along a two-lane highway RCU80. Calculate the minimum length of the curve based on minimum required Stopping Sight Distance (SSD). Assume the height of driver's eye = 1.05 m and the height of object = 0.380 m.

(b) If the tangents of the above highway intersect at station 200 + 15, calculate the stations of the BVC (beginning of vertical curve) and EVC (End of Vertical Curve)

**(The distance between stations in this problem is 30 m)**

2. A two-lane highway UCU80 is 7.5 m wide with a cross-slope of 0.02 m/m. A point of intersection (PI) exists at station 30+000.000 with a deflection angle of  $25^\circ$ . A horizontal circular curve is required to connect the two tangents (without spiral).

Design the curve and develop the superelevation (max of 0.04 m/m) by rotating about its center line. Use horizontal scale of 1 to 500 and a vertical scale of 1:5. Show and calculate the stations at

- a) the beginning of the tangent runout
- b) the junction of tangent to transition length
- c) the beginning of the circular curve
- d) the end of the circular curve

**(the distance between stations is 1000 m)**

3. (a) A minor road intersects a 7.5 m wide two-lane highway URU80 where the intersection is controlled by a stop sign. Calculate the required minimum sight distance along the major road (URU80) from the intersection based on the following:
  - Perception and reaction time of the driver is 2.5 seconds
  - Distance from the near edge of the pavement of URU80 to the front of the stopped vehicle = 3.0 m
  - Assume single unit trucks or buses (SU-9) with a length of 9.1 m traveling on the minor road

(b) Describe the possible reasons for each of the following types of pavement distress and state whether the distress is classified as structural or functional:

**For Asphalt Pavement:**

- (i) Bleeding
- (ii) Fatigue cracking
- (iii) Polished aggregate
- (iv) Rutting

**For Concrete Pavement:**

- (i) D-cracking
- (ii) Pumping
- (iii) Map cracking

**Table B.3.1.4a**  
**Superelevation and minimum spiral parameter,  $e_{max} = 0.04$  m/m**

design speed, km/h	40		50		60		70		80		90		100	
radius, m	$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4		$\frac{A}{2}$ 3&4	
	e	lane lane	e	lane lane	e	lane lane	e	lane lane	e	lane lane	e	lane lane	e	lane lane
7000	NC		NC		NC		NC		NC		NC		NC	
5000	NC		NC		NC		NC		NC		NC		NC	
4000	NC		NC		NC		NC		NC		NC		NC	
3000	NC		NC		NC		NC		NC		NC		RC 410	410
2000	NC		NC		NC		NC		RC 300	300	RC 315	315	RC 335	335
1500	NC		NC		NC		RC 240	240	RC 260	260	RC 275	275	.022	290 290
1200	NC		NC		NC		RC 215	215	RC 230	230	.021	245 245	.026	260 260
1000	NC		NC		RC 180	180	RC 200	200	.020	210 210	.025	225 225	.030	235 235
900	NC		NC		RC 175	175	RC 190	190	.021	200 200	.027	210 210	.032	225 225
800	NC		NC		RC 165	165	RC 180	180	.023	190 190	.029	200 200	.034	210 210
700	NC		RC 140	140	RC 150	150	.020	165 165	.026	175 175	.032	185 185	.036	200 200
600	NC		RC 130	130	RC 140	140	.023	155 155	.029	165 165	.035	175 175	.039	190 190
500	NC		RC 120	120	.021	130 130	.026	140 140	.033	150 150	.038	160 160	.040	190 190
400	RC 95	95	RC 105	105	.025	115 115	.031	125 125	.037	135 135	.040	160 160	.040	190 190
350	RC 90	90	.020	100 100	.027	110 110	.033	120 120	.039	135 135	.040	160 160	min R=490	
300	RC 80	80	.023	90 90	.031	100 100	.036	110 110	.040	135 135	min R=380			
250	RC 75	75	.026	85 85	.034	90 90	.038	110 110	.040	135 135	min R=280			
220	RC 70	70	.029	80 80	.036	90 90	.039	110 110	min R=280					
200	.021	65 65	.031	75 75	.038	90 90	min R=280							
180	.023	65 65	.033	70 70	.039	90 90	min R=280							
160	.025	60 60	.035	70 70	.040	90 90	min R=200							
140	.028	55 55	.037	70 70	.040	90 90	min R=200							
120	.031	50 55	.039	70 70	min R=150									
100	.034	50 50	.040	70 70	min R=150									
90	.036	50 50	.040	70 70	min R=150									
80	.038	50 50	min R=100											
70	.040	50 50	min R=100											
60	.040	50 50	min R=100											
	.040	50 50	min R=60											

$e_{max} = 0.04$

**Notes**

- e is superelevation
- A is spiral parameter in metres
- NC is normal cross section
- RC is remove adverse crown and superelevate at normal rate
- Spiral length,  $L = A^2 + \text{Radius}$
- Spiral parameters are minimum and higher values may be used
- For 6-lane pavement: above the dashed line use 4-lane values, below the dashed line use 4-lane values  $\times 1.15$ .
- A divided road having a median less than 3 m may be treated as a single pavement.

4. A flexible pavement section is to be designed for four-lane highway (two lanes in each direction) with a one-way average daily traffic (ADT) of 8000, truck volume of 5%, and an annual growth in traffic volume of 2% over the design period of 20 years. The pavement is to be constructed on a subgrade with modulus of resilience of 34.5 MPa or 5000 psi.
- Calculate the total truck volume in the **design lane** over the design period
  - If the average Equivalent Single Axle Load (ESAL) per truck is 2 ESAL, calculate the design ESAL
  - Assuming a flexible pavement that consist of 100 mm asphalt concrete with a layer coefficient of 0.42, 300 mm road base with a layer coefficient of 0.14, and 400 mm subbase with layer a layer coefficient of 0.10: use AASHTO method to check if this pavement is adequate for the intended traffic and design period. Assume a reliability of 90%, an overall standard deviation  $S_o$  of 0.49, an initial serviceability of 4.5 and terminal serviceability of 2.6.
5. (a) The following is a gradation of subgrade soil. The subbase material planned to be used has a  $D_{15}$  of 2.1 mm. Check if subgrade intrusion (subgrade intrudes into subbase) will be an issue if this subbase is used

Sieve Size	Passing
2.0 mm	100%
300 um	85%
150 um	60%
75 um	42%
40 um	15%

- (b) Smooth plastic pipe of 4 inches in diameter with roughness coefficient of 0.01 is placed at 2.5% slope in a trench drain. If outlets are provided every 300 ft, what is the maximum allowable lateral inflow into the plastic pipe in  $\text{ft}^3/\text{day}/\text{ft}$ .
6. (a) The bulk density of an asphalt concrete mix was determined experimentally and found to be  $2366 \text{ kg}/\text{m}^3$ . The maximum density is  $2448 \text{ kg}/\text{m}^3$ . The specifications require air voids content within the range of 3% to 5% and a percent voids filled with asphalt (VFA) in the range from 65% to 75%. Check if this mix meets the specified volumetric requirements given the following:
- Asphalt content = 5.5% (expressed as % of total mix)
  - Relative density of combined aggregates = 2.65
  - Relative density of asphalt = 1.04
- (b) Specifications require a 95% subgrade compaction on a project. Maximum dry density and the optimum moisture content were determined in the lab and found to be  $1800 \text{ kg}/\text{m}^3$  and 9%, respectively. Results from the field test showed a wet density of  $1850 \text{ kg}/\text{m}^3$  and a moisture content of 12%. Is the compaction satisfactory?

7. (a) Draw a graph to show the effect of traffic or age on serviceability or structural capacity of a flexible pavement with a design period of 20 years. On the same graph, show the effect of an overlay constructed at the end of the 20 years on serviceability, and the effects of traffic over the following 15 years (no values are needed).

(b) A condition survey was carried out on an existing flexible pavements and the following layer coefficients were assigned to each of the layer as follows:

Layer	Thickness	Coefficient
Asphalt concrete	100 mm	0.32
Roadbase	300 mm	0.10
Subbase	400 mm	0.08

- Calculate the effective structural number of the pavement
- Calculate the required thickness of asphalt overlay if the future structural number is 120 mm. Assume a layer coefficient of 0.42 for new asphalt layer.

(c) A concrete mix has a compressive strength of 5000 psi. Estimate the modulus of rupture and the modulus of elasticity of this mix.